

# Printer Specifications

Print Technology	Drop-on-demand thermal inkjet printing
Print speed	Up to 5 ips (speed varies depending on the size of the label, print mode and label registration type selected)
Print Quality	Up to 4800 x 1200 optimized dpi
Ink Cartridges	There are four large, separate ink cartridges in the VP485 (Cyan, Magenta, Yellow and Black) Each ink cartridge can be replaced separately. Ink levels are displayed on the printers display
Compatible Operating Systems	Microsoft Windows 2000 XP, Windows 7 and Vista
Media Dimensions	- Maximum Label / Tag roll width 8.5" - Label roll on a 3" core - External roll maximum diameter 10" - Minimum label height 1" - Minimum label width 1.5"
Media Handling	Gap sensing and black mark sensing Continuous label or tag stock Handles roll or fanfold stocks
Adjustable registration	The registration mark sensor is adjustable across the label width to allow for sensing of different shapes
Options	- Automatic cutter module (Available second quarter of 2010) - Ethernet base 10/100 base T (Available on request) - Integrated rewinder unit (Available on request) - Integrated pin fed option for form handling
Dimensions / Weight	Printer: 19.4 (W) x 14.1 (D) x 11.5 (H) Inches 495 (W) x 360 (D) x 294 (H) mm 25 lbs.
Interfaces	USB II (optional ethernet)